

	A	B	C	D	E	F	G
1	OHIO MICROWAVE INVENTORY OF RF AND MICROWAVE COMPONENTS - 06 April 2017						
2							
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
4	M/A-COM	2088-0000-02	Adapter	SMA M-F Right Angle, DC-12.4 GHz	1	36	
5	M/A-COM	3281-2241-00	Adapter	BNC Male to SMA Male	2	46	
6	Greenpar	520-8432	Adapter	TNCM to screw-on cable	120	4	
7	Greenpar	8845-96-0153/520-8433	Adapter	TNC Female to TNC Reverse Polarity Jack (Female center pin), Also Greenpar G512	20	1	
8	Pasternack	PE9144	Adapter	SMA Male to SMB Plug	4	AC	
9	Pasternack	PE9421	Adapter	BNC Female to UHF Female	2	B	
10	RF Connectors	RSA-3477	Adapter	SMA Female to N Female, Microwave	2	C	
11	Delta	SMCJ-SSMAJ	Adapter	SMC Jack to SSMA Jack	77	46	
12	M/A-COM	504052	Adapter, Waveguide	WR90 Flat Flange to WR90 Choke Flange, straight, aluminum, microwave	3	46	
13	M/A-COM	3100-6255-00	Adapter, WG-Coax	WR62-TNCF, 12.4-18GHz	1	29	
14	M/A-COM	4201-6110-00	Adapter??	Unknown microwave adapter type	1	29	
15	M/A-COM	AM-1035	Amplifier	TO-8, 297-303 MHz, Gain=17 dB, 1dB Comp Pt=+19dBm, NF=3.5, GE 7548484 Pacer Dawn	1	36	5962014255935
16	M/A-COM	AM-1035	Amplifier	TO-8, 297-303 MHz, Gain=17 dB, 1dB Comp Pt=+19dBm, NF=3.5, GE 7548484 Pacer Dawn	4	37	5962014255935
17	M/A-COM	AM-1061	Amplifier	TO-8, IAW 807132-1 Lockheed Martin Drawing	4	33	5962012575442
18	M/A-COM	AM-1117	Amplifier	Martin Marietta 1GWX101, TO-8	3	8	
19	M/A-COM	AM-1198	Amplifier	Unknown RF amplifier	1	36	
20	M/A-COM	AM-1239	Amplifier	IAW (97871)420-00399-01,260-560 MHz,15dB Gain,6dB NF,4 pins+center pole, test data	2	2	
21	M/A-COM	AM-1307	Amplifier	10-200MHz, 8.2 dB Gain, NF 2.5, Emerson P/N CS118411	4	22	
22	M/A-COM	AM-1358	Amplifier	Thin Film, For E-Systems, 551-10040-001,10-2000MHz,Gain10dB,+7dBm 1dB Comp, NF=6	1	8	
23	M/A-COM	AM-1359	Amplifier	Unknown RF amplifier	1	20	
24	M/A-COM	AM-1360	Amplifier	Unknown RF amplifier	10	30	
25	M/A-COM	AM-1361	Amplifier	Made for Qualcomm	8	30	
26	M/A-COM	AM-1365	Amplifier	260-560 MHz, E-systems 420-0038501	4	30	
27	M/A-COM	AM-1367	Amplifier	TO-8, 5-500MHz, 12 dB Gain, 7 NF, +19 dBm 1dB comp	1	32	
28	M/A-COM	AM-1367	Amplifier	5-500MHz, 15V@100mA,12 dB Gain, +19dBm 1 dB comp, GEC Ferranti 28661-31205	2	33	
29	M/A-COM	AM-1372	Amplifier	TO-8, 30-250 MHz, 8.2 gain, 3.5 nf, +20 2 dB comp, Bias +15@60 mA	1	32	
30	M/A-COM	AM-1372	Amplifier	30-250MHz, 8.2 dB Gain, Ferranti UK 28611-31025, NF 3.5 dB, +20 dBm 1 dB Cmp Pt	1	33	
31	M/A-COM	AM-1383AM	Amplifier	SMA, 821-851 MHz, Class A, GaAsFET, NF 1.5 dB, Gain 44 dB, Output IP3 +34 dBm, VSWR 1.5/2.0 I/O, +24 VDC @ 200 mA (internally regulated to 15 VDC), KS-21583L7, Comcode 407103332	30	13	
32	M/A-COM	AM-142 PIN	Amplifier	Low Noise, 200-1000MHz, Gain 12 dB, NF 3.8 dB, TO-8-1 package, data sheet	3	5	5996013583482
33	M/A-COM	AM-1452	Amplifier	TO-8, 15-500 MHz, 17 dB Gain, GEC Marconi, 15 VDC @ 60 mA, 50 Ohms 28661-3120	1	33	
34	M/A-COM	AM-149 PIN	Amplifier	DIP Package, military system, -55 to +85 C Deg	10	37	5962012809278
35	M/A-COM	AM-151 T1B	Amplifier	5-500MHz, 12 dB gain, 7 dB NF, +19 dBm 1 dB pt, TO-8-1, data sheet, ES8725-01	1	30	5996014672177
36	M/A-COM	AM-179 PIN	Amplifier	Cascadable Thin Film, TO-8-1	35	20	
37	M/A-COM	AM40-0023	Amplifier	Ultra low-noise pHEMT Dual Channel, 1.71-1.91 GHz, Gain 14 dB, NF 0.7 dB, surface mount, data sheet available	6	33	
38	M/A-COM	AM61-0001	Amplifier	1710-1910 MHz, 12 dB Gain, +7VDC, Tiny, NF 0.9dB, IIP 0 dBm	2	33	
39	M/A-COM	AM85-0004-SMA	Amplifier	SMA, +12 VDC	1	32	
40	M/A-COM	AM-956	Amplifier	Unknown specifications	6	30	
41	Agilent	MGA-72543	Amplifier	PHEMT, GaAs MMIC, 0.1-6 GHz Switched, DC0045, Microwave	2296	25	
42	KDI	AY-G14S	Amplifier, Receiver Combiner	1.850-1.910Ghz, 20.5 dB Gain, 3 inputs/1 output, TDMA, Noise Figure 6.9 dB Max, Max output +11dBm, Max input +8dBm, SMA Female, 12VDC@375 mA, 5.00 X 3.00 X 0.56 inches, Full Data Sheet Available. Transcept Part Number 1000353	85	50	
43	KDI	AY-G318	Amplifier, Receiver Combiner	1.850-1.910Ghz, 20.5 dB Gain, 2 inputs/1 output, TDMA, Noise Figure 5.1 dB Max, Max output +11dBm, Max input +8dBm, SMA Female, 12VDC@375 mA, 5.00 X 3.00 X 0.56 inches, Full Data Sheet Available.	11	50	
44	M/A-COM	3368-8000	Antenna	AN325 Flat Plate, Double Ridge WG feed, WRD-1" wide	1	29	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
45	M/A-COM	3375-8003-0012	Antenna	3094AS5128-3, coax fed, for Navy AN/DSQ-51	29	28	
46	M/A-COM	3380-8009-0002	Antenna	1765AS0400-1, SMA Connector, 55 Watts Peak	8	28	5985013266843
47	M/A-COM	3380-8026-0005	Antenna	416.5 MHz, GDSS PN 57-03204-4, F04701-88-C-0042, Airplane use, TNC F Feed	1	29	
48	M/A-COM	3380-8026-0006	Antenna	416.5 MHz, Airplane Flange Mount, Coax fed, LMA PN 57-03204-5	1	28	
49	M/A-COM	3380-8030-0028	Antenna	Omni X-band, coax fed, flange mount, microwave	1	28	
50	M/A-COM	3380-8030-0049	Antenna	With 8" coax, no connector	22	30	
51	M/A-COM	3380-8030-0075	Antenna	GSM Array, flat, 18" coax lead with N Male right angle, SAP PN 466190A-101	9	30	
52	M/A-COM	3380-8030-0103-10	Antenna	Black Plastic 4" long, RG316 with Small Right Angle push on connector	5	27	
53	M/A-COM	3380-8030-0137	Antenna	GPS??? 4" coax with tiny connector, for FEDEX	7	27	
54	M/A-COM	3395-8015-0054	Antenna	Flat, with 2 Nmale cables attached	1	31	
55	M/A-COM	3396-8010-0013	Antenna	Flat Plate, 11" coax with N Male connector	10	30	
56	M/A-COM	3396-8010-0021	Antenna	Flat Plate, 3" diameter, N Female connector	1	A	
57	M/A-COM	3710-8000	Antenna	12813-625885-1, FRPA-2, F04701-79-C-0085, flat plate, coax feed	1	29	
58	M/A-COM	ANAD-159W-A-10-SM	Antenna	2300-2500 MHz, 12" Square, Wall Mt, P/N AVNET 60027007, SMA Male with 10" coax	1	44	
59	M/A-COM	ANCC-156A-S-12-NM	Antenna	Omnidirectional, 15" high rod w/12" coax and NM Connector, White, 2.4-2.5 GHz, Gain 7dB	4	43	
60	M/A-COM	ANP-C-109-4	Antenna	Coax feed, 2 7/8 dia Patch, Made for Second Source	12	6	
61	M/A-COM	ANP-C-174G-P-O-SF	Antenna	Pico Cell, 1850-1990 MHz, SMA Female, with mounting hardware	1	A	
62	Nextek	PTR7AFONF60S	Arrester	Sureguard Gas tube protector, 7/16 Female to N Female Bulkhead, DC-2 GHz, 1600 max watts, Protection Voltage 600V. Call or e-mail for datasheet.	126	50	
63	Nextek	QWSNA7A5.800K	Arrester	Lightning Arrester, 1/4 wave stub, 5.655-5.945 GHz, 7/16 Female to N Female bulkhead, data sheet available.	754	50	
64	M/A-COM	9522-6012-04	Attenuator	Chip, 4 dB	25	21	
65	M/A-COM	9552-6011-01	Attenuator	Chip, 1 dB	288	20	
66	M/A-COM	AV00022-04	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 4 dB Have Data Sheet	3900	22	
67	M/A-COM	AV00022-05	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 5 dB Have Data Sheet	1865	22	
68	M/A-COM	AV00022-08	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 8 dB Have Data Sheet	640	22	
69	M/A-COM	AV00022-09	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 9 dB Have Data Sheet	120	22	
70	M/A-COM	AV00022-11	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 11 dB Have Data Sheet	609	22	
71	M/A-COM	AV00022-12	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 12 dB Have Data Sheet	32	22	
72	M/A-COM	AV00022-16	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 16 dB Have Data Sheet	100	22	
73	M/A-COM	AV00022-19	Attenuator	Mountable Die/Chip, DC-2.5 GHz, 2 W @25C, 0.2 W @ 125C, 19 dB Have Data Sheet	100	22	
74	M/A-COM	1082-4002-40	Attenuator, Fixed	SSMA M-F, 0.5 dB, DC-12.4 GHz	12	20	
75	M/A-COM	1082-4003-40	Attenuator, Fixed	SSMA M-F, 1 dB, DC-12.4 GHz	12	20	
76	M/A-COM	1082-4004-40	Attenuator, Fixed	SSMA M-F, 1.5 dB, DC-12.4 GHz	11	20	
77	M/A-COM	1082-4005-40	Attenuator, Fixed	SSMA M-F, 2 dB, DC-12.4 GHz	7	20	
78	M/A-COM	2082-4135-06S	Attenuator, Fixed	SMA, 6 dB, DC-12.4, 2 Watts, M3933/14C-02S	8	A	5985013926235
79	M/A-COM	2082-4135-07S	Attenuator, Fixed	SMA, 7 dB, DC-12.4, 2 Watts, M3933/14C-10S Screened	2	26	
80	M/A-COM	2082-4135-08S	Attenuator, Fixed	SMA, 8 dB, DC-12.4, 2 Watts, M3933/14-11S	1	12	5985011557841
81	M/A-COM	2082-4135-11S	Attenuator, Fixed	SMA, 11 dB, DC-12.4, 2 Watts, M3933/14-22S	6	A	
82	M/A-COM	2082-4135-13S	Attenuator, Fixed	SMA, 13 dB, DC-12.4, 2 Watts, M3933/14-20S, Screened	3	12	
83	M/A-COM	2082-4135-16N	Attenuator, Fixed	SMA, 16 dB, DC-12.4, 2 watts, M3933/14C-18N	1	26	
84	M/A-COM	2082-4135-16S	Attenuator, Fixed	SMA, 16 dB, DC-12.4, 2 watts, M3933/14C-18S Screened	16	13	
85	M/A-COM	2082-4137-00S	Attenuator, Fixed	SMA, 0 dB, DC-18, 2 Watts, M3933/16-16S Screened	31	15	5985013045375
86	M/A-COM	2082-4137-14S	Attenuator, Fixed	SMA, 14 dB, DC-18, 2 Watts, M3933/16C-34S, Screened	1	26	
87	M/A-COM	2082-4137-16S	Attenuator, Fixed	SMA, 16 dB, DC-18, 2 Watts M3933/16C-38S Screened	6	27	5985014631205
88	M/A-COM	2082-4137-18S	Attenuator, Fixed	SMA, 18 dB, DC-18, 2 Watts, M3933/16-42S, Screened	3	10	
89	M/A-COM	2082-4261-08	Attenuator, Fixed	SMA, 4 dB, DC-12.4, 2 Watts, IAW (82577)H970065-011B, 0.86", VSWR 1.15	4	3	5985014334733
90	M/A-COM	2082-4261-12	Attenuator, Fixed	SMA, 4.5 dB, DC-12.4, 2 watts, Hughes H970065-015B, 0.86", VSWR 1.15	5	26	5985014334735
91	M/A-COM	2082-4383-07S	Attenuator, Fixed	SMA, 7 dB, DC-12, 2 watts, M3933/25-33S Screened	2	26	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
92	M/A-COM	2082-4384-02S	Attenuator, Fixed	SMA, 2 dB, DC-2, 2 watts, M3933/25-02S Screened	1	26	5985013153282
93	M/A-COM	2082-4384-07S	Attenuator, Fixed	SMA, 7 dB, DC-2, 2 Watts, M3933/25-07S Screened	25	10	
94	M/A-COM	2082-4384-09S	Attenuator, Fixed	SMA, 9 dB, DC-2, 2 Watts, M3933/25-09S Screened	29	11	
95	M/A-COM	2082-4384-15N	Attenuator, Fixed	SMA, 15 dB, DC-2, 2 Watts, M3933/25-15N	15	27	5985014067253
96	M/A-COM	2082-4384-17S	Attenuator, Fixed	SMA, 17 dB, DC-2, 2 Watts, M3933/25-17S, Screened	2	20	
97	M/A-COM	2082-4385-04S	Attenuator, Fixed	SMA, 3.5 +/-0.2dB, DC-18, 2 Watts, M3933/16-20S, Screened	4	21	
98	M/A-COM	2082-4385-06S	Attenuator, Fixed	SMA, 5.5 dB, DC-18, 2 watts, M3933/16C-22S	9	30	5985014617020
99	M/A-COM	2082-4385-12S	Attenuator, Fixed	SMA, 11.5 dB, DC-18, 2 Watts, M3933/16C-29S, Screened	19	9	
100	M/A-COM	2082-4385-14S	Attenuator, Fixed	SMA, 13.5 dB, DC-18, 2 Watts, M3933/16C-33S, Screened	2	9	
101	M/A-COM	2082-4472-40	Attenuator, Fixed	SMA, Azusa 1331516-4 Rev E	3	27	
102	M/A-COM	2082-4473-40	Attenuator, Fixed	SMA, microwave, unknown value	5	27	
103	M/A-COM	2082-4476-40	Attenuator, Fixed	SMA, microwave	6	27	
104	M/A-COM	2082-4477-40	Attenuator, Fixed	SMA, Azusa 1331516-14 Rev E	1	27	
105	M/A-COM	2082-4478-40	Attenuator, Fixed	SMA, Aerojet Azusa 1331516-16 Rev E	5	27	
106	M/A-COM	2082-4479-40	Attenuator, Fixed	SMA, Aerojet Azusa 70143-1331516-18 Rev E, Space	2	24	
107	M/A-COM	2082-4622-51	Attenuator, Fixed	SMA, 11 dB, DC-18, Aerojet Azusa 1331516-21 Rev E	3	24	
108	M/A-COM	2082-4622-52	Attenuator, Fixed	SMA, Aerojet Azusa 70143-1331516-22 Rev E, Space	1	24	
109	M/A-COM	2082-4640-40	Attenuator, Fixed	SMA, EMS 37957-818063-114	6	24	
110	M/A-COM	2082-4642-40	Attenuator, Fixed	SMA, EMS 37957-818063-154	5	24	
111	M/A-COM	2082-5801-40	Attenuator, Fixed	SMA, microwave	4	46	
112	M/A-COM	2082-6013-11	Attenuator, Fixed	SMA, 11 dB, DC-4, 2 Watts	3	26	
113	M/A-COM	2082-6013-13	Attenuator, Fixed	SMA, 13 dB, DC-4, 2 Watts	1	21	
114	M/A-COM	2082-6013-14	Attenuator, Fixed	SMA, 14 dB, DC-4, 2 Watts	1	26	
115	M/A-COM	2082-6020-00	Attenuator, Fixed	SMA, 0 dB, DC-18 GHz, 2 Watts, VSWR 1.35 @ 18	6	21	
116	M/A-COM	2082-6131-04	Attenuator, Fixed	SMA F-F, 4.5 dB, DC-18, 2 Watts	1	21	
117	M/A-COM	2082-6141-00	Attenuator, Fixed	SMA, 0 dB, DC-18, 2 Watts	162	3	5985013306515
118	M/A-COM	2082-6143-08	Attenuator, Fixed	SMA, 8 dB, DC-18, 2 Watts	18	41	5985013408761
119	M/A-COM	2082-6144-12	Attenuator, Fixed	SMA, 12 dB, DC-18, 2 watts	1	21	5985013412358
120	M/A-COM	2082-6173-07	Attenuator, Fixed	SMA, 7 dB, DC-4, 2 Watts, L=1.24 inches	307	1	
121	M/A-COM	2082-6173-08	Attenuator, Fixed	SMA, 8 dB, DC-4, 2 Watts, L=1.24 inches	2	26	
122	M/A-COM	2082-6173-09	Attenuator, Fixed	SMA, 9 dB, DC-4, 2 Watts, L=1.24 inches	5	21	
123	M/A-COM	2082-6183-07	Attenuator, Fixed	SMA, 7 dB, DC-12.4, 2 Watts	21	3	
124	M/A-COM	2082-6183-08	Attenuator, Fixed	SMA, 8 dB, DC-12.4, 2 Watts, L = 1.24 inches	290	3	
125	M/A-COM	2082-6184-11	Attenuator, Fixed	SMA, 11 dB, DC-12.4	2	21	
126	M/A-COM	2082-6184-12	Attenuator, Fixed	SMA, 12 dB, DC-12.4	2	21	
127	M/A-COM	2082-6184-16	Attenuator, Fixed	SMA, 16 dB, DC-12.4	2	21	
128	M/A-COM	2082-6184-19	Attenuator, Fixed	SMA, 19 dB, DC-12.4	1	21	
129	M/A-COM	2082-6188-06	Attenuator, Fixed	SMA, 6.5 dB, DC-12.4	1	21	
130	M/A-COM	2084-6174-20	Attenuator, Fixed	SMA F-F, 20 dB Flange Mount, DC-4 GHz	2	21	
131	M/A-COM	3282-6171-01	Attenuator, Fixed	BNC, 1 dB, DC-4, 2 Watts	93	1	
132	M/A-COM	5182-4001-10	Attenuator, Fixed	OSSP, 10 dB, Plug-Jack	5	26	
133	Huber Suhner	6606.19.AC	Attenuator, Fixed	SMA, 6 dB, DC-2.2 GHz, 2 Watts	89	46	
134	Huber Suhner	6806.01.AC	Attenuator, Fixed	BNC, 6 dB, DC-2.2 GHz, 2 Watts, 50 Ohm	10	45	
135	Huber Suhner	6806.26.AC	Attenuator, Fixed	TNC, 6 dB, DC-2.2 GHz, 2 Watts, 50 Ohm+D176	57	45	
136	M/A-COM	8P141-012W-268	Attenuator, Fixed	SMA, 6 dB, DC-12.4, Hi-Rel	8	26	
137	Midwest Microwave	ATT-0294-06-SMA-02	Attenuator, Fixed	SMA, 6 dB, DC-2 GHz, 2 Watts	2	46	5985014938456
138	Mini-Circuits	BW-S2W2	Attenuator, Fixed	SMA, 2 dB, DC-18 GHz, SMA, 2 Watts	166	36	5985015382194
139	M/A-COM	AT10-0006	Attenuator, Variable	Digital, Surface Mount	8	33	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
140	M/A-COM	AT-103	Attenuator, Variable	20-1000MHz, digital, 15.5 dB in .5 dB steps, CMOS control, 5-bit, DI-3 pkg, data sheet	2	33	
141	M/A-COM	AT-560	Attenuator, Variable	Voltage variable, 35 dB, 10-1000 MHz, 15-0 VDC, 1342AS909	16	37	5962013815231
142	M/A-COM	AT65-0001	Attenuator, Variable	Digital, TTL Driver	7	20	
143	HH Smith	211-103	Banana Plug	Now Abbatron, Color Black, Sold In Packs Of 5	70	34	
144	Microlab FXR	HW-E32	Bias Tee/DC Block	N Male RF, N Female RF + DC, BNC DC In, 1.7-2.3 GHz, 100 Watts, 50 Volts@2amps, Full Data Sheet Available Transcept 1000204	185	50	
145	M/A-COM	4598-6007-00	Body, Plug	SMA, microwave	10	29	
146	M/A-COM	1313913-1	Cable Assembly	F Female Bulkhead to OSMT Plug, RG179, 7 inches, 58A90H009000, with boots, more in 42	400	43	
147	M/A-COM	1538-8389-2156	Cable Assembly	H-P, SMA Male to ??, Green Coax, Looks like N Male but different, microwave	1	29	
148	Unknown	447795-001	Cable Assembly	SMA Male to TNC Female Panel Mt, Belden 1855A, 16.5 inches, with boots	511	810	
149	Unknown	447795-002	Cable Assembly	SMA Male to TNC Female Panel Mt, Belden 1855A, 13.25 inches, with boots	203	810	
150	Unknown	447796-001	Cable Assembly	MCX RA Plug to MCX RA Plug, RG405 Conformable Flex, 5.5 inches, with boots	158	810	
151	Unknown	447796-002	Cable Assembly	MCX RA Plug to MCX RA Plug, RG405 Conformable Flex, 15.5 inches, with boots	105	25	
152	M/A-COM	58A90H009000	Cable Assembly	F Female Bulkhead to OSMT Plug, RG179, Also PN 9411-5187-00, 7 inches, with boots, more in Bin 43	110	42	
153	Radiall	850401-5	Cable Assembly	Semi-rigid, multi-curved, SMA Male to SMA Female, copper line	5	42	
154	M/A-COM	8630-96-0253	Cable Assembly	N Male, RG142, 9.5 inches, No connector on other end (cable trimmed)	3	45	
155	M/A-COM	8630-96-1054	Cable Assembly	N Male, RG142, 7.5 inches, No connector on other end (cable trimmed)	13	45	
156	Radiall	993960X1	Cable Assembly	SMA Male Right Angle to SMA Female Bulkhead, 59 inches	6	7	
157	M/A-COM	9950-1125-23	Cable Assembly	Tiny right angle pushons, 5 "	80	30	
158	Winchester	CA008-002	Cable Assembly	MCX RA Plug to MCX RA Plug, RG316, 5.8 inches, with boots, Data Sheet	2418	810	
159	Winchester	CA008-003	Cable Assembly	MCX RA Plug to MCX RA Plug, RG316, 14.5 inches with boots, Data Sheet	586	310	
160	Pasternack	PE33261-72	Cable Assembly	SMB Plug Right Angle to SMB Jack Bulkhead, RG-174, 50 Ohms, 72 Inches	12	36	
161	Sparta	SPCA-248-0010	Cable Assembly	F Female panel mount, RG179, to tiny pushon, 10 inches	500	37	
162	M/A-COM	1020-1311-02	Cap	SSMA Jack, Stainless	19	26	
163	M/A-COM	1021-1310-00	Cap	SSMA Plug, with chain, gold plated	11	26	
164	M/A-COM	1021-1310-02	Cap	SSMA Male with chain, Stainless	1	21	
165	M/A-COM	1298-4003-40	Cap	2-Hole Flange Mount ? ? ? ? ?	871	5	
166	M/A-COM	2020-1310-00	Cap	SMA Jack with chain	5	26	
167	M/A-COM	2020-1311-00	Cap	SMA Jack	1	11	5935014282786
168	M/A-COM	2021-1310-02	Cap	SMA Male with chain, also 5340-01-390-1193, passivated stainless steel	1908	18	5935011017890
169	M/A-COM	2021-5093-31	Cap	SMA Male	2	22	
170	M/A-COM	2021-5099-02	Cap	SMA Male with chain, passivated stainless steel	7	42	
171	M/A-COM	2061-03-0102	Cap	Female ????	45	34	
172	M/A-COM	3000-03-0102	Cap	BNC Female	4	34	
173	M/A-COM	3002-1310-02	Cap	N Jack with chain	4	41	
174	M/A-COM	3002-4002-02	Cap	N Female with chain	1	26	
175	M/A-COM	3060-03-0202-7	Cap	BNC Female	153	34	
176	M/A-COM	3101-1310-02	Cap	TNC Plug with chain	3	26	
177	M/A-COM	3101-1315-02	Cap	TNC Plug, L=0.60, D/C=0030	73	18	5935012549451
178	M/A-COM	3102-4013-02	Cap	TNC Female with chain, also in Bin 22	1	21	
179	M/A-COM	3102-4013-02	Cap	TNC Female with chain, also in Bin 21	2	22	
180	M/A-COM	3201-1315-02	Cap	BNC Male	2	26	
181	M/A-COM	3202-1315-02	Cap	BNC Jack	116	41	
182	Bendix	M39012/25-0006	Cap	BNC Male, with chain	5	46	5985008852264
183	M/A-COM	2021-5099-02	Cap Or Short	SMA Male with chain	5	22	
184	M/A-COM	7N045	Circulator	N, 5 x 5 x 1.25 inches, Cellular band	3	30	
185	M/A-COM	7N127A	Circulator	N	6	25	
186	M/A-COM	7N164	Circulator	N, Port 1+3 N straight, Port 2 N 90 degrees, Cellular Band	30	32	
187	M/A-COM	7N165-S003	Circulator	TNCF on 1 and 2, TNCM on 3, MA79165, Cellular Band	64	9	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
188	M/A-COM	7N248-C4	Circulator	Drop In, 1890-1930, 20/.35/1.2,25W,,75X.75X.33	8	8	
189	M/A-COM	7N256-S014	Circulator	Drop-In, Flange Mount, cellular, 1"X1", Isol 24, IL 0.25, 65W Forward, 30W Reverse, 5% BW	208	15	
190	M/A-COM	7N256-S014	Circulator	Drop-In, Flange Mount, cellular, 1"X1", Isol 24, IL 0.25, 65W Forward, 30W Reverse, 5% BW	96	42	
191	M/A-COM	7N256-S014	Circulator	Drop-In, Flange Mount, cellular, 1"X1", Isol 24, IL 0.25, 65W Forward, 30W Reverse, 5% BW	6	A	
192	M/A-COM	7N264-S011	Circulator	DropIn, 1805-1880, 22/.35/1.20, 65 Watts	41	15	
193	M/A-COM	7R056	Circulator	Triple Junction	1	20	
194	M/A-COM	7R190-S002	Circulator	Dual Junction, 504-455 MHz, NF, 3.75X2.00X1.00, 24/0.3/1.2, 200 Watts	4	41	
195	M/A-COM	C650C	Circulator	SMA, 4-8 GHz, 17/.6/1.35, .75X.75X.375	4	33	
196	DiTom	DF6520	Circulator	865-900 MHz, N Female, 500 Watts, 1.38 X 1.65 X 1.27 In. I.L.=0.3dB, VSWR 1.22, Isol 22 dB	39	D	
197	M/A-COM	H360-450-SMA	Circulator	SMA In/Out, NF Port 3, 1.75X1.875X1.00, tunable 360-450 MHz, 125 Watts	6	41	
198	Gilbert	0119-750-1	Connector	GPO Male Limited Det, Shrd to PC Board	500	2	
199	ITT Cannon	051-045-0000-220	Connector	SMB Jack Bulkhead to Solder Cup, DC-4 GHz	29	46	
200	M/A-COM	1052-4001-40	Connector	SSMA Female 4-Hole Flange Mount, Captive Contact, with O-ring gasket	4	20	
201	AMP	1053354-1	Connector	SMA Female Straight for PC Board, Captured Center Contact, Straight Terminal See also MACOM part number 2062-0000-00	72	46	
202	Huber Suhner	11N-50-8-11/133 UE	Connector	N Male Straight for Corrugated Cable, DC-11 GHz, Cable type 4, EFX2-50	6	46	
203	Delta	12130000071-3	Connector	TNC Female, 4-Hole Flange Mount, Solder Cup	222	5	
204	Delta	1259-000-N091-7	Connector	TNCM Flange Mt, bifurcated pin, 508-927-106	219	16	
205	Delta	1313-000-K921-7	Connector	SMA Female, 2-hole flange mount, solder cup	4	46	
206	EF Johnson	142-0403-001	Connector	SMA Plug Assy Crimp for RG316, 161, 174, 188, 316. Gold-Plated Brass. Have Date Sheet	46	2	
207	M/A-COM	1538-1634	Connector	M39012/03-0012, KN-19-114 97 18, N Female for Cable Mount	1	42	
208	M/A-COM	1550-0164	Connector	SMA Female, 18 GHz, Connector Head	75	31	
209	M/A-COM	2001-5003-02	Connector	SMA Male Direct Solder for .141 semirigid cable, with contact, OSM207-1SF	11	46	5935006326345
210	M/A-COM	2001-5209-40	Connector	SMA Male to Semi-Rigid Cable Also 2A004-033V-001	19	4	
211	M/A-COM	2001-7941-00	Connector	SMA Male, Gold Plated, Direct Solder for .085 and .141	8	2	
212	M/A-COM	2004-4001-40	Connector	SMA Female Panel Mount for cable attachment	51	4	
213	M/A-COM	2007-4013-40	Connector	SMA Male Right Angle for cable, solder attachment	23	4	
214	M/A-COM	2007-7941-00	Connector	SMA Male Right Angle for .141Semi-rigid cable, Solid TFE, DC-12.4 GHz, Gold body and connector	2	46	
215	M/A-COM	2007-7941-02	Connector	SMA Male Right Angle for .141Semi-rigid cable, Solid TFE, DC-12.4 GHz, Gold body, stainless connector	11	46	
216	M/A-COM	2032-5026-02	Connector	SMA Female Crimp for RG178, RG196, with .312 Hex OSM602-5SF D/C95	533	31	
217	M/A-COM	2034-5078-40	Connector	SMA Female Panel Mount for cable crimp	36	4	
218	M/A-COM	2037-4023-42	Connector	SMA Male Right Angle for cable	1	27	
219	M/A-COM	2037-4026-40	Connector	SMA Male Right Angle Crimp	33	4	
220	M/A-COM	2051-5386-00	Connector	SMA Male Flange to female pin	17	10	
221	M/A-COM	2052-0125-40	Connector	SMA Female 4 Hole Flange Mount, w/solder hole on inside	15	2	
222	M/A-COM	2052-0680-40	Connector	SMA Flange Mt, Dielectric 7/16, Pin 1/8	42	4	
223	M/A-COM	2052-1215-02	Connector	SMA Female flange mount, Captured Center Contact, Dielectric 0.125 inches, for microstrip	9	46	
224	M/A-COM	2052-4069-40	Connector	SMA F Flange Mount to pin	15	27	
225	M/A-COM	2052-4096-41	Connector	SMA F Flange Mount, Dielectric 9/16, Center 1/8"	25	2	
226	M/A-COM	2052-5756-02	Connector	SMA Jack Flange Mount to solder cup, 2-Hole Flange	33	31	
227	M/A-COM	2053-5050-00	Connector	SMA Male Right Angle Flange Mount to 1/2 inch pin	20	5	
228	M/A-COM	2054-4033-40	Connector	SMA Female Flange Mount Right angle, dielectric 9/16, pn 5/8	79	27	
229	M/A-COM	2056-5006-00	Connector	SMA Female bulkhead feedthru, Solder Pot Terminal, Captured Center Contact	6	46	
230	M/A-COM	2057-3244-00	Connector	SMA Male Hermetic Panel Feedthru, Metal-Metal Seal (Spark Plug)	6	46	
231	M/A-COM	2058-3425-02	Connector	SMA Male Hermetic Panel Feedthru	29	2	
232	M/A-COM	2058-4002-40	Connector	SMA Female Panel Mount to Pin	4	27	
233	M/A-COM	2058-5517-02	Connector	SMA Female	14	46	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
234	M/A-COM	2058-5560-02	Connector	Unknown SMA Type	45	46	
235	M/A-COM	2062-0000-00	Connector	SMA Female Straight Vertical Mount for PC Board, Captured Center Contact, Straight Terminal See also AMP part number 1053354-1	72	46	
236	AMP	221789-1	Connector	SMA Jack, Vertical, PCB Mount, 4 GHz	224	9	
237	M/A-COM	2367-0000-54	Connector	OSMT Surface Mount PC Board Plug Receptacle	94	43	
238	M/A-COM	2501863-2	Connector	Mini-15 pin D sub, Panel to PC Board	16	45	
239	Specialty Connector	25PR137-1	Connector	N Male Flange Mount with bifurcated pin, bulk packaged	50	19	
240	Specialty Connector	25PR137-1	Connector	N Male Flange Mount with bifurcated pin, individually packaged, also PN 633705-3	134	2	
241	Specialty Connector	25PR137-1	Connector	N Male Flange Mount with bifurcated pin, individually packaged, also PN 633705-3	50	1	
242	M/A-COM	299-99-00-156	Connector	BNC Female straight for PCB mount, solder cup contact	35	42	
243	M/A-COM	3052-0000-10	Connector	N Female Flange, Solder Pot, Nickel Plated Brass	3	4	5935013739798
244	M/A-COM	3101-5270-02	Connector	TNC Male for cable, Crimp	24	9	
245	M/A-COM	3102-4027-41	Connector	TNC Female for Cable	25	13	
246	M/A-COM	3395-0579	Connector	TNC Jack flange mount to pin	118	37	
247	M/A-COM	3396-0579	Connector	TNC Jack Flange Mount to pin	10	46	
248	Dynawave	3752-0081-6220	Connector	SMC Jack, 2-hole flange mount, DC-36 GHz,Field Replaceable, Accepts 0.015 dia pin, data sheet	14	46	5935013549763
249	M/A-COM	43608-44-420-1	Connector	TNC Jack Flange Mount to 7/16 inch long pin	5	46	
250	M/A-COM	4541-5001-02	Connector	OSP Plug flange mount to coax, right angle	15	37	
251	M/A-COM	4557-5048-02	Connector	OSP Plug	10	45	
252	Delta	508-927-1060	Connector	N Male Flange Mount, bifurcated pin.	8	4	
253	M/A-COM	509662-2	Connector	SMA Jack Right Angle flange mount to pin	1	46	
254	Seaelectro	51-307-3850	Connector	SSMB For Cable Attachment	38	46	
255	CDI	5450CCSF	Connector	SMAF swept right angle flange mount, dielectric 9/16, solder pin 0.05", DC-26.5 GHz	9	42	
256	M/A-COM	5837-5002-10	Connector	OSX/MCX Right Angle Plug for RG178/RG196, packs of 50 w/instructions, Nickel Plated	626	31	
257	M/A-COM	5862-5002-10	Connector	OSX/MCX Straight Jack, PCB Mount, Captured Center Contact, Nickel Plated	13	45	
258	CDI	5964-480-2CC	Connector	SMA Female Bulkhead Feedthru "spark plug" Hermetic seal, to pin (drawing available)	104	46	
259	Delta	628665-1	Connector	TNCF Flange Mt, bifurcated pin	20	3	
260	Amphenol	901-143	Connector	SMA Female Right Angle for PC Board	24	46	5935011348478
261	M/A-COM	9056-5014-00	Connector	Tiny, Unknown Type	116	45	
262	M/A-COM	9662-5000-10	Connector	1361169-1 unknown type	2	16	
263	M/A-COM	CN-0009-SMA	Connector	SMA Female for cable attachment	13	22	
264	M/A-COM	CN01-0001-40S	Connector	SMA Male, Artemis Program, Space, PN SA/ART/0541/TPR-01-B	12	22	
265	M/A-COM	CN01-0002-40S	Connector	SMA Male for cable	5	22	
266	M/A-COM	CN10-0002-SMA	Connector	SMA Female to ??	24	46	
267	M/A-COM	CN10-0006-SMA	Connector	SMA, microwave	32	1	
268	M/A-COM	CN10-0007-SMA	Connector	SMA Male Right Angle for Cable	11	22	
269	M/A-COM	CN10-0008-SMA	Connector	SMA Male for cable	7	22	
270	M/A-COM	CN10-0010-SMA	Connector	SMA Female for cable attachment	19	22	
271	M/A-COM	CN10-0011-SMA	Connector	SMAF Bulkhead, Solder Cup	23	22	
272	M/A-COM	CN10-0017-S	Connector	SMA Female	184	5	
273	M/A-COM	CN52-0004-40	Connector	SMAF Flange Mount, Flat Tab 3/16" long, Stainless Steel	14	22	
274	M/A-COM	CN52-0005-40	Connector	SMAF Flange Mount, Dielectric 1.5 cm, pin 1.6 cm, Gold Plated	13	22	
275	M/A-COM	CN57-0002-40	Connector	SMAF Flange Mount, Dielectric 1.5 cm, pin 0.3 cm, Gold Plated	21	22	
276	M/A-COM	CN58-0002-40	Connector	SMAF P/N FPS652160, Space	10	22	
277	M/A-COM	CN64-0001-40	Connector	SMA Female Bulkhead Right Angle PC Board Mount	3	22	
278	M/A-COM	CN98-0002-40	Connector	Possibly feedthrough?	34	4	
279	Kings	KN-19-114	Connector	M39012/03-0012, KN-19-114, N Female for Cable Mount	1	46	5935005997902
280	Pasternack	PE4015	Connector	BNC Female Bulkhead up to 1/4" panel thickness, Solder Cup Contact	8	A	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
281	Pasternack	PE4118	Connector	SMA Female Right Angle PC Mount	1	B	
282	Midwest Microwave	SMA-6040-19-003-02	Connector	SMA Male straight, microwave	104	31	
283	Tru Connector	TRU-6978-SSU	Connector	N Male for M/A-COM FE35RPL Cable, but will work with others. Hex nut.	75	41	
284	Tru Connector	TRU-9111	Connector	BNC Male Straight, Captive contact, Clamp, RG55, 58, 141, 142, 223, 400. Silverplated brass	45	46	
285	Unknown	Unknown	Connector	N Female to pin, Press Fit	404	16	
286	M/A-COM	4598-6005-00	Contact	Plug for SSMA	24	15	
287	M/A-COM	8628-11-0101	Contact	Small gold contacts	589	43	
288	Wiltron	SC5210	Contact	Sliding Contact, CN98-0001-41	38	22	
289	M/A-COM	SA-560	Converter, Frequency	Dual Downconverter Module, IAW 96214-2901907-3(H), RFIN1160-1360MHz	1	20	5895013224941
290	M/A-COM	CH20-0007-FP1	Coupler	Flatpack	2	22	
291	M/A-COM	CH20-0008-FP2	Coupler	Flatpack, 53711-L6815983	1	28	
292	M/A-COM	CH20-0035-8GSAM	Coupler	Surface Mount	3	22	
293	M/A-COM	CH-752	Coupler	Coupler	2	26	
294	M/A-COM	CH-794	Coupler	Bidirectional	1	28	
295	M/A-COM	2020-4274-43	Coupler, Directional	SMA Male in, Female out and coupled, 3282077-1	2	27	
296	M/A-COM	2020-4332-43	Coupler, Directional	SMA, 20028543P1, C-Band Transmit	1	27	
297	M/A-COM	2020-4333-43	Coupler, Directional	SMA, 20028543P2, C-Band Transmit	1	27	
298	M/A-COM	2025-4108-41	Coupler, Directional	SMA, 10 dB, 823-923 MHz	14	2	
299	M/A-COM	CH20-0032-17G SAM	Coupler, Directional	Bi-directional, SMA, 824-960, 17 dB	2	5	
300	M/A-COM	CH-684	Coupler, Directional	SMA, 11.25 dB, 100-300 MHz	2	28	
301	M/A-COM	CH-702	Coupler, Directional	Bidirectional, 10-500MHz, 10dB, flatpack, H970075-001B	5	28	5985012453132
302	Mini-Circuits	ZADC-13-2000-1	Coupler, Directional	SMA, 13 dB, 800MHz to2GHz, Insertion Loss 0.8 dB	2	D	
303	NARDA	3322	Coupler, Directional, Hybrid	0.82-0.98 GHz, 90 Deg, N, 3 dB, 500 W, CEL3322, Cellular	70	D	
304	Sage Labs	HCB1-0.97	Coupler, Wireline	Wireline coupler, 0.97" semirigid, copper, no connectors, details at sage.com	368	45	
305	M/A-COM	2044-4014-00	DC Block	SMA M/F, Inside/Outside, Bendix 11746645, 200V, 1-4 GHz	1	21	
306	Wall Industries	JRW48D15-330I	DC-DC Converter	TWN, Input=18-75VDC, Output=+/-15VDC @ 330mA, Data Sheet Available	663	510	
307	Wall Industries	SPW48S9-50	DC-DC Converter	Input=18-75VDC, Output=9VDC @ 5.55A, Data Sheet Available	466	110	
308	M/A-COM	SA65-0002	Delay Line	Delay Line	117	20	
309	M/A-COM	2085-4019-00	Detector	SMA F-F, negative output, microwave	3	29	
310	M/A-COM	2086-4062-00	Detector	SMA F-F, Negative output, Ferranti P/N 61010686-00, Zero Bias	7	37	
311	M/A-COM	7700K-0104	Detector	SMA, Tunnel Diode, 9-10 GHz, 97942 Westinghouse/N>G> 583R263H01, Positive output	1	37	5895010783334
312	M/A-COM	PD-S5002	Detector	Hughes PN 4F23-001FHA	5	23	
313	M/A-COM	PD-121 G PIN	Detector, Phase	3-200 MHz, Output Polarity Positive, Flatpack	5	21	
314	M/A-COM	PD-121 TIA	Detector, Phase	3-200 MHz, flatpack	7	21	
315	Motorola	1N4003	Diode	Silicon Rectifier, 200 PIV, 1 Amp, Leads 1.125 inches each side	50	22	5961011269560
316	Agilent	HSMP-3804-TR1	Diode, PIN	Attenuator, Base B, SOT23 Package, Tape and reel, DC0036, Price \$1.00 each	2117	25	
317	M/A-COM	DP52-0002 SAM	Diplexer	Dual Band, 824-960 and 1850-1990, SO-8 pkg	3	36	
318	M/A-COM	DP52-0005 SAM	Diplexer	Specs unknown	4	36	
319	M/A-COM	3089-6001-00	Divider	2-Way NF, 3.625-4.275 Ghz, 2.0X1.25X1.0	9	2	
320	RLC	402 738 405	Divider	8-Way, SMA, Cellular band	2	C	
321	CMCI	7SP301-2	Divider	2-Way, SMA, 7-14.5 GHz, IL=0.6dB, ISOL=19dB, AmpBal=+/-0.3, Phase 5 deg, 1X1X0.5 inches	25	36	
322	M/A-COM	8654-8004	Divider	2-Way TNC, (11556 CAGE Code)	3	29	
323	RLC	D-1053	Divider	2-Way, N Female, Cellular band	2	C	
324	M/A-COM	DS-1090	Divider	CPN TPR-30-011-01B Cassini Program	2	23	
325	M/A-COM	DS-1093	Divider	8 leads	1	24	6625012518891
326	M/A-COM	DS-1126	Divider	2-way, flatpack, 10-2000MHz	5	28	
327	M/A-COM	DS-1151	Divider	2-way, 10-500 MHz, flatpack	3	26	
328	M/A-COM	DS-1160	Divider	3-way, flatpack	2	28	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
329	M/A-COM	DS-1175	Divider	IAW 772441-1 (96214 -- Texas Instruments)	1	29	5895012904838
330	M/A-COM	DS-1356	Divider	3-Way, TO-8, 390-405MHz, TI 1980252-1 Complete data and ATP	32	28	
331	M/A-COM	DS-1356	Divider	3-Way, TO-8, 390-405MHz, TI 1980252-1 Complete data and ATP	3	29	
332	M/A-COM	DS-1398	Divider	4-way, flat pack, 70-1000 MHz	18	28	
333	M/A-COM	DS-1408	Divider	2-way, Loral, flatpack, 10-600 MHz, -55 to +85 Deg C, IAW 145A531-1	4	28	
334	M/A-COM	DS-1416	Divider	2-way, TO-8, 310-480 MHz, TI PN 1980265-0002, 7 Matched sets of 3 each	21	28	
335	M/A-COM	DS-1443G	Divider	Flatpack, 1-300 MHz	7	24	
336	M/A-COM	DS-1501	Divider	Space Qualified Flatpack	1	24	
337	M/A-COM	DS-1558	Divider	2-way, flatpack	11	28	
338	M/A-COM	DS-1565	Divider	TO, 1-100 MHz	2	24	
339	M/A-COM	DS-310-T1	Divider	4-way, 0.2-300MHz, flatpack, data sheet available, Isol 25 dB, Plase +/- 4 Deg, Amp +/- 0.2	3	28	5985011015962
340	M/A-COM	DS-312 TNC	Divider	4-way, 10-500 MHz, TNC, 1 watt	8	28	
341	M/A-COM	DS-415PIN	Divider	Specs unknown	1	22	
342	M/A-COM	DS52-0001 SAM	Divider	2-way, 824-960 MHz, On evaluation Board with SMA Female connectors	2	37	
343	M/A-COM	DS52-0004 SAM	Divider	2-Way, 1510-1660, SO-8 package	1	36	
344	M/A-COM	DS52-0005 SAM	Divider	2-way, SMT, 1700 to 1900 MHz, SO-8 Package on board with SMA Female connectors	2	37	
345	M/A-COM	DS52-0012	Divider	Surface Mount, 900 MHz	100	22	
346	M/A-COM	DS53004	Divider	SMT, SOIC-8	61	37	
347	M/A-COM	DS54-0001SAM	Divider	4-Way, SMA, 824-960 MHz	2	5	
348	M/A-COM	DS54-0003SAM	Divider	4-Way, SMT, 1.200-1.660 GHz	1	22	
349	M/A-COM	DS54-0043SAM	Divider	4-Way, 2200-2500, On PC Board with SMA connections	2	22	
350	M/A-COM	DS56-0001 SAM	Divider	6-Way, SMA, 824-960 MHz	1	5	
351	M/A-COM	DS56-0002 SAM	Divider	6-Way, SMT, 1.7-2.0 GHz	1	22	
352	M/A-COM	DS56-0003	Divider	6-Way, SMT, 2200-2500MHz, marking 9623012	25	29	
353	M/A-COM	DS56-0003 SAM	Divider	6-Way, SMT, 1200-1660 MHz	3	22	
354	M/A-COM	DS-834	Divider	2-way, flatpack, 10-500 MHz, Allied Signal 2132713-1 with data	2	21	
355	M/A-COM	DSS-113 T1A	Divider	2-Way, 400kHz-400MHz, SF-1 Surface Mount, Hermetic, Have Data Sheet	5	28	
356	M/A-COM	DSS-113 T1Z	Divider	2-Way, 400kHz-400MHz, SF-1 Surface Mount, Hermetic, DC 2000, Have Data Sheet	3	28	
357	M/A-COM	PD10-0005-FP2	Divider	20-2000MHz, Customer P/N 87001B3458	1	22	
358	M/A-COM	PD10-0013 SMA	Divider	2-way, SMA	3	28	
359	M/A-COM	PD10-0014-RH1	Divider	2-way, 8-pin DIP	7	28	
360	M/A-COM	PD10-0015-T08	Divider	2-way Divider	4	22	
361	M/A-COM	PD10-0018-FP2	Divider	2-way, 780 MHz, flatpack	3	28	
362	M/A-COM	PD10-0025-S	Divider	Surface Mount, Bosch Telecom RA.3003.003.10 Issue C	8	23	
363	M/A-COM	PD10-0026-SMA	Divider	2-Way, SMA, 70-180 MHz, Raytheon G226079-1	5	22	6625011758517
364	M/A-COM	PD20-0007-FP2	Divider	3-way, .2=200MHz, flatpack, CPN G435001	1	26	
365	M/A-COM	PD25-0005-FP5	Divider	4-way, 450-700 MHz, flatpack	3	28	
366	M/A-COM	PD25-0012-SF5	Divider	4-way flatpack	3	28	
367	M/A-COM	PD89-0002-02S	Divider	2-Way SMA	4	20	
368	M/A-COM	PD89-0002-02S	Divider	2-Way SMA	1	22	
369	M/A-COM	PDD-0004-TO5	Divider	Specs unknown	1	22	
370	MCLI	PS2-29	Divider	2-Way SMA, 10-15 GHz	1	A	
371	M/A-COM	PS53-0002SAM	Divider	SMT	3	22	
372	MCLI	SM-A-989239	Divider	4-Way, N Female, 7-8 GHz, Data Sheet Available	2	C	6625012240363
373	Minicircuits	ZAPD-2	Divider	2-Way SMA, 1-2 GHz	146	44	5895012297431
374	Minicircuits	ZCSC-8-1	Divider	8-Way SMA, 2-250 MHz	19	7	5895014958803
375	NARDA	2362-2	Divider/Combiner	1.8-2.0 GHz, 2-Way, N, 80 Watts	51	D	
376	MECA	H2N.0-900	Divider/Combiner	0.8-1.0 GHz, 2-Way, N, 80 Watts	9	7	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
377	Clearcomm	CCDP-205	Duplexer	5.8 GHz Data Link Duplexer, SMA, CH1 = 5.725-5.773GHz, GH2 = 5.802-5.850GHz, 10 Watts Avg, 100 Watts Peak, Full data sheet available. ISM Band, Transcept Part Number 1000145	371	50	
378	Clearcomm	CCDP-330	Duplexer	Upper PCS Band High Power, TX to Ant=1.950-1.990GHz, RX to Ant=1.850-1.910Ghz, Rx SMA Female, TX N Female, Ant N Female, 150 Watts Avg, 1500 Watts Peak, Full Data Sheet Available. Transcept Part Number 1000438	214	50	
379	Tek-Wave	10-1237-0000	Feedthru, Hermetic	Also P/N 850583-1, Tek-Wave was part of FEI	500	4	
380	FerriShield	BC28B1251	Ferrite Suppressor	Ferrite Suppressor 3/4 ID, Cable Bundle Clamp, specs at www.ferrishield.com	128	50	
381	M/A-COM	5KBC10-437.5/U75	Filter	Probably 437.5 MHz Communications	69	43	
382	M/A-COM	8631-002	Filter	LC, Surface mount, Argtx 400	64	42	
383	M/A-COM	8632-002	Filter	LC surface mount	132	42	
384	M/A-COM	8632-003	Filter	LC, Surface Mount	75	43	
385	Clearcomm	CCRF-69	Filter	Receive, PCS Full Band TDMA, 1.850 to 1.910 GHz, SMA Female, 1 Watt Average, 10 Watts Peak, Full Data Sheet Available. Transcept Part Number 1000230+D861	137	50	
386	IMC	IMC9	Filter	IMC9, IMC60656, 922352	125	19	
387	RLC	BPF-500-140-50-4-R	Filter, Bandpass	1/2 Inch Tubular, CF 140 MHz, 3dB BW 50 MHz, 4 Sections, SMA	1	A	
388	RLC	BPF-500-350-60-4-R	Filter, Bandpass	1/2 Inch Tubular, CF 350 MHz, 3dB BW 60 MHz, 4 Sections, SMA	1	A	
389	RLC	BPF-500-70-48-4-R	Filter, Bandpass	1/2 Inch Tubular. CF 70 MHz, 3dB BW 48 MHz, 4 Sections, SMA	1	A	
390	M/A-COM	FL05-0002-GSAM	Filter, High Pass	TO-8, Rejection DC-100=20 dB, 1700-3000 = 0.5 dB insertion, Mounted on board with SMA connectors. Data Sheet	3	22	
391	M/A-COM	FL07-0001-GSAM	Filter, Low Pass	Passband DC-1000 MHz, Rejection 1800-3500, SOIC-8 package, Mounted on board with SMA connectors. Data Sheet	1	22	
392	M/A-COM	FL07-0002G SAM	Filter, Low Pass	SMA Low Pass, DC-6, I.L. 0.6 dB @ DC-2, 20 dB @ 3500-6000, Mounted on board with SMA connectors. Data Sheet	2	5	
393	M/A-COM	7KCB30-1375/U850	Filter??	850 MHz Communications Band	99	43	
394	M/A-COM	2032-4153-41	Hybrid	3 dB, 4-port SMA, 4947027	1	27	
395	M/A-COM	2032-4157-43	Hybrid	3 dB, 4-port SMA, 2629983-2	2	27	
396	M/A-COM	2032-4177-00	Hybrid	SMA, 3 dB, 180 Deg 4 port, 2-4 GHz, CPN 2629861-3	1	A	
397	M/A-COM	HH-633	Hybrid	180 deg, 20-2000MHz, flatpack	4	28	
398	M/A-COM	HY03-0001-FP2	Hybrid	180 deg, 20-200 MHz, Flatpack, TRW 36-194006-1	7	28	
399	M/A-COM	JH-598B	Hybrid	8-pin package	2	21	
400	M/A-COM	JH-631	Hybrid	90 deg, TI HARM Missile application, TI PN 899947-1	30	28	5915012592044
401	M/A-COM	JH-685	Hybrid	90 deg 4-port, 20-40 MHz, TO, 97942-645A526H02	2	28	5985012710831
402	M/A-COM	JH-689	Hybrid	90 deg, 20-40 MHz, Raytheon 5526931-1	2	28	
403	M/A-COM	JH-722	Hybrid	SMA, 4-port, CPN X30BA042HM001, 3 space flight hardware and 2 non-flight	5	23	
404	M/A-COM	JH-770	Hybrid	90 degrees, 1.2-1.4 GHz IL 0.3, Isol 20, Amp Bal 1 dB, Phase Bal +/- e Deg, Have Acceptance test data	22	28	
405	M/A-COM	JH-800	Hybrid	Quad Hybrid, 8-pin flat pack, CPN CI-STP-1006 Rev B	9	23	
406	M/A-COM	JH-S5009	Hybrid	Flat pack	2	23	
407	M/A-COM	JH-S5010	Hybrid	Quadrature, 8-Pin flatpack, POTL3027-01B	21	23	
408	M/A-COM	QH-01-0005-SF1	Hybrid	Quadrature, flatpack, 68 MHz, Magnavox 388625	6	28	
409	M/A-COM	QH02-0001-S	Hybrid	Quadrature Hybrid, RA.3003.004.10 Bosch Telecom	2	23	
410	Analog Devices	AD8052AR	IC	Dual High Speed Rail-Rail Amplifier, SOIC Pkg, T&R, DC0107	1460	810	
411	Analog Devices	AD8052-AR0034-I44475	IC	Dual High Speed Rail-Rail Amplifier, SOIC Pkg, In Tubes, Not T&R	939	25	
412	AMD	AM2602PC-8428DMP	IC	Price = \$1.50 each	100	910	
413	Lattice Semicon	GAL22V10B025LP	IC	Hi-Performance E2CMOS PLD, Generic Array Logic, DC9741	75	910	
414	Motorola	MMBZ5229BLT1	IC	Zener Voltage Regulators, SOT-23 Surface Mount, Tape & Reel, DC9919	7283	25	
415	Ferrocom	2100-2T	Isolator	WR42, 20.9-23.9 GHz, Isolation 23, IL 0.20	1	B	
416	Ferrocom	40B45-05	Isolator	SMA, 5.9-7.125 GHz, Port 1 female, port 2 male	11	B	
417	Ferrocom	40B45-05	Isolator	SMA, 5.9-7.125 GHz, Both ports female	2	C	
418	M/A-COM	7L301	Isolator	SMA, Cardion PN 12909-402907	2	26	
419	M/A-COM	7L601-S002	Isolator	SMA	1	25	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
420	M/A-COM	7N201-50	Isolator	SMAM In, SMAF Rt Angle Out, 1GDW-101, 1X1X.5, 900 MHz Cellular Band	63	17	
421	M/A-COM	7N201-50	Isolator	SMAM In, SMAF Rt Angle Out, 1GDW-101, 1X1X.5, 900 MHz Cellular Band	84	34	
422	M/A-COM	7N248-S031	Isolator	Drop-In, 25 Watts, .75X.75X.33, somewhere between 1755 and 1990 MHz	25	31	
423	M/A-COM	7N248-S031	Isolator	Drop-In, 25 Watts, .75X.75X.33, somewhere between 1755 and 1990 MHz	11	46	
424	M/A-COM	7N256-T-B2	Isolator	Drop-In, 1.54-1.58 GHz, Isol 23 dB, I.L. 0.3 dB, VSWR 1.20, DC9552 have swept data plots	2	26	
425	M/A-COM	7R204-S001	Isolator	Dual Junction Flange Mount, 921-960 MHz, Isolation 50 dB, Insertion Loss 0.3 dB, VSWR 1.21:1 Max, Ericsson Part Number KRY1011542/1 Revision E	125	8	
426	Alcatel	9C52-15	Isolator	NF in, NM out, 1840-1990 MHz, 20dB Isolation, 25 watts	1	36	
427	M/A-COM	C650T	Isolator	SMA, 4-8 GHz, 17/.6/1.35, .75X.75X.375	7	A	
428	UTE Microwave	CD-5650-ST	Isolator	Drop-In, 5.4-5.9 GHz	140	48	
429	M/A-COM	F800T	Isolator	Ferropill, 8-12 GHz, 16/0.7/1.4, DC9248, have test data sheet	11	26	
430	M/A-COM	H360T-450	Isolator	NF, 125 Watts,w/ 20 Watt Termination MA44001, tunable 406-512 MHz	7	4	
431	M/A-COM	IT1107-L1	Isolator	SMA, 1.009-1.11 GHz, 17 dB, IL-0.5 dB, 12 Watts, Rockwell Collins PN 13499-277-0336-020	2	26	
432	Pamtech	KHG1020-10	Isolator	WR42 Dual Junction. Full Band 18.0-26.5 GHz, Isolation >40 dB, IL <0.90	1	A	
433	M/A-COM	M2B1537-S011	Isolator	SMA	1	32	
434	M/A-COM	MA8K679T	Isolator	WR-42, Termination is on Port 1, microwave	2	29	
435	M/A-COM	R800T	Isolator	Drop-In	28	A	
436	M/A-COM	2690-9071	Limiter	SMA, IL 0.1, Leakage 8 dBm @ +20 dBm	1	21	
437	M/A-COM	2690-9088	Limiter	SMA, 1-2GHz, Flat Leak +20, 1 dB comp +5dBm, 400W, .1usec, .001 Du	2	21	
438	M/A-COM	2690-9089	Limiter	SMA M-F, .5-1 GHz, Flat leak +20 dBm@400W, .1 usec, .001Du	3	21	
439	M/A-COM	2690-9091	Limiter	SMA Male-Male	3	21	
440	M/A-COM	2300D 0210-01	Mixer	SMA	2	46	
441	FEI	2300D-0210-01	Mixer	SMA	7	45	
442	M/A-COM	2901-11-DBL	Mixer	RF: 6-18 GHz @ -10 dBm, IF: 100 MHz, LO: 6.1-18.1 GHz @ +7 and +11 dBm. Have acceptance test data sheet from M/A-COM. Package size approx 0.50 X 0.50 Inch.	3	29	
443	M/A-COM	2902-04-DBM	Mixer	Double Balanced, Removable SMA Connectors, 2-18, IF .01-6, Have Data Sheet	1	24	
444	M/A-COM	2902-10-DBH	Mixer	Miniature Open Substrate, 2-18, IF .5-8 GHz, Have Data Sheet	6	24	
445	M/A-COM	2902-10-DBM	Mixer	Double Balanced, 2-18 GHz, IF .5-8 GHz, Open Substrate, Have Data Sheet	4	24	
446	M/A-COM	3601-07-DBH	Mixer	4-18 GHz, IF DC-1.0, LO Power +15 dBm	5	24	
447	M/A-COM	DM1-8A	Mixer	SMA, Double Balanced	4	24	
448	RHG Laboratories	DMEX2-18	Mixer	Double Balanced, 4-18 GHz, SMA	1	24	5985012574164
449	M/A-COM	IRDS1-4/00	Mixer	SMA 4-port, RFIN, 2 IFIN,RFOUT	1	29	
450	M/A-COM	IRR5.9/30-36	Mixer	QUIET, SMA, built-in preamp, 5.4-5.9 GHz	1	36	
451	Marki Microwave	M98162	Mixer	E-Carrier Mixer, LO 2.4 GHz, RF 3.65 to 4.35 GHz, IF 1.25 to 1.95 GHz. Have Data Sheet	35	42	
452	M/A-COM	MA1103A-5026	Mixer	Hughes 82577-653309, WR90 HH	2	30	5985012451282
453	M/A-COM	MAC-50	Mixer	Double Balanced, TO-5-2, RF/LO 0.2-200 MHz, IF DC-200 MHz, Conversion Loss 5.0 dB Typ, LO Drive +7, Have Data Sheet	44	37	5962010405578
454	M/A-COM	MAF-4067-00	Mixer	LO/RF 2-18.5 GHz, IF DC-150MHz, Honeywell 10115272-101	1	30	5985012980122
455	M/A-COM	MAF-4089	Mixer	Specs unknown	23	27	
456	M/A-COM	MD-100 PIN	Mixer	RF/LO 1-400 MHz, IF DC-400 MHz, Conversion Loss 6.0 dB, LO Drive +13 dBm, 1 dB Comp Point +7 dBm, RH-3 Package, Have Data Sheet	186	15	
457	M/A-COM	MD-1099	Mixer	SMA, 50-1500, 1-3, 2-4 GHz, 78E6N3328, ALT-40, flatpack	1	27	5895013361831
458	M/A-COM	MD-110 TIA	Mixer	RF/LO 10-1000 MHz, IF DC-1000, LO Drive +7 dBm, Conversion Loss 6.5 dB, Have Data Sheet	8	27	
459	M/A-COM	MD-1119	Mixer	SMA AR50127-314-00-8 B	3	27	
460	M/A-COM	MD-113 TIA	Mixer	Double Balanced, RF/LO 5-1000MHz, IF DC-1000, LO Drive +7, Conversion Loss 6.6 dB, 1 dB Comp Point 0 dBm, TO-8-1, data sheet	6	27	6625010619917
461	M/A-COM	MD-1131	Mixer	5 MHz - 1 GHz, flatpack, Martin Marietta	1	27	5895012736748
462	M/A-COM	MD-1154	Mixer	Martin Marietta	3	27	
463	M/A-COM	MD-1163	Mixer	Martin Marietta	14	27	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
464	M/A-COM	MD-1175	Mixer	SMA, Rockwell	9	27	
465	M/A-COM	MD-1196	Mixer	BAE Systems 333501	2	27	5895014125934
466	M/A-COM	MD-123 TI	Mixer	RF/LO/IF 10 MHz-3 GHz, FP-2 flat pack, LO Drive +10 dBm, 1 dB Comp Point +7 dBm, Conversion Loss 7.4 dB	1	27	
467	M/A-COM	MD-124-TIA	Mixer	Flat Pack, Double Balanced, RF/LO 0.5-500 MHz RF, IF=DC-500, LO Drive +7, Conversion Loss 5.6 dB, 1dB Comp Point +2 dBm, Have Data Sheet	5	24	5895014938394
468	M/A-COM	MD-1264	Mixer	SMA Connectors, microwave	3	36	
469	M/A-COM	MD-1272	Mixer	Flatpack, RF 990-1190, LO 930-1130, IF 30-100, Westinghouse PN 1A20038H01	4	36	
470	M/A-COM	MD-1327	Mixer	Flat pack	1	27	
471	M/A-COM	MD-1361	Mixer	CPN ELH002-101-Y202 Rev P2	11	23	
472	M/A-COM	MD-143 BNC	Mixer	RF/LO 5-500 MHz, IF DC-500 MHz, LO Drive +7, Conversion Loss 5.6 dB, 1dB Comp Point +2.5 dBm, BNC Female Connectors, Have Data Sheet	9	24	5895011996732
473	M/A-COM	MD-1434	Mixer	SMA	1	27	
474	M/A-COM	MD-1436	Mixer	ESCO	20	27	
475	M/A-COM	MD-1445	Mixer	SMA, CPN 89 M-635-P002	1	36	
476	M/A-COM	MD-146 PIN	Mixer	RF/LO = 5-500 MHz, IF = DC-500 MHz, RH-3 Package, LO Drive +7 dBm, Conversion Loss 5.6 dB, 1dB Comp Point +2.5, Have Date Sheet	602	9	
477	M/A-COM	MD-1479	Mixer	TRW	5	27	
478	M/A-COM	MD-148 PIN	Mixer	FP-2 Flat Pack, RF/LO=10-1500, IF=DC-1500MHz, Have Catalog Data Sheet, LO Drive +10 dBm, Conversion Loss 10-800 @ 7.5 dB Max, 8000-1500 @ 10 dB Max, Isolation 40 dB, Input P1dB=+5 dBm	6	27	5895013724314
479	M/A-COM	MD-1490	Mixer	IAW Hewlett-Packard 0955-0525RevA	17	1	
480	M/A-COM	MD-1491 TIB	Mixer	Double Balanced, 10-1500 MHz	3	27	
481	M/A-COM	MD-1492	Mixer	Double Balanced, CPN 8P344-003S-637	3	23	
482	M/A-COM	MD-1495	Mixer	RF 10-3700 MHz, LO 310-4000, L-3 Comm P/N 7181313-001 Rev B	2	37	
483	M/A-COM	MD-1543	Mixer	SMA, RF 3.1-3.6 GHz, LO 4.4-4.9, IF 1.20-1.40, Customer PN 68X-160-P002 Have Test Data	2	37	
484	M/A-COM	MD-156	Mixer	RF/LO 0.6-3 GHz, IF=DC-1000, Double Balanced, FP-2 flatpack, Conversion Loss 800-2000 @ 8 dB, 600-3000 @ 9 dB, LO Drive +7 dBm, Have Catalog Data Sheet	2	46	5895011544729
485	M/A-COM	MD-1562	Mixer	Navy 1472AS511, DC 96	254	41	
486	M/A-COM	MD-157	Mixer	RF/LO 0.8-4.0 GHz, IF DC-1500 MHz, LO Drive +7, Conversion Loss 5.8 dB, 1dB Comp Point 0 dBm, Hermetically Sealed FP-2 flatpack	5	27	5895012425698
487	M/A-COM	MD-1590	Mixer	Surface Mount, Raytheon	1	27	
488	M/A-COM	MD-1592	Mixer	Mixer	1	27	
489	M/A-COM	MD-1597	Mixer	Double Balanced, Spec 8P350-002U-517 Rev D	13	23	
490	M/A-COM	MD-1598	Mixer	Double Balanced, CPN 8P344-006V0517 RevA	10	23	
491	M/A-COM	MD-1599	Mixer	2.6-5.2 GHz, IF DC-300, GEC/Marconi H200A246-201	7	37	
492	M/A-COM	MD-165 PIN	Mixer	Mixer, Specifications Unknown	21	24	
493	M/A-COM	MD-166	Mixer	Flat pack	15	30	
494	M/A-COM	MD-169 TIB	Mixer	Termination Insensitive, FP2, .001-3.5GHz, IF=5-1500MHz, IAW 19200-12604346 Have Army Dwg	1	27	5895011537634
495	M/A-COM	MD-170PIN	Mixer	Unknown	7	24	
496	M/A-COM	MD-174 TIB	Mixer	Flat Pack, RF/LO=1-2800, IF=1-2000MHz	3	27	5895011878280
497	M/A-COM	MD-174G PIN	Mixer	Surface Mount, E-Systems	8	27	
498	M/A-COM	MD-186PIN	Mixer	Specs unknown	9	24	
499	M/A-COM	MD-1951	Mixer	Mixer, Flatpack	2	27	
500	M/A-COM	MD20-0002	Mixer	Loral, Microwave	6	27	
501	M/A-COM	MD20-0004-PB8	Mixer	Mack Associates	3	27	
502	M/A-COM	MD20-0009-S	Mixer	589R237H03	4	23	
503	M/A-COM	MD20-0010S	Mixer	589R237H02	7	23	
504	M/A-COM	MD20-0011S	Mixer	589R237H01	8	23	
505	M/A-COM	MD20-0012-MU7	Mixer	Mixer	5	24	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
506	M/A-COM	MD20-0014-S	Mixer	Bosch Telecom RA.3003.001.10 Issue B	6	23	
507	M/A-COM	MD25-0002-PB9	Mixer	Mixer	8	27	
508	M/A-COM	MD33-0012-PB7	Mixer	RF 1.2-1.4, LO 1.75-1.96, IF 553 MHz, CPN 68X-253, 10-Pin flat pack, with data	2	36	
509	M/A-COM	MD33-0013-FP2	Mixer	RF/LO=1-3500MHz, IF=5-1500 MHz, flatpack	8	36	
510	M/A-COM	MD-4007	Mixer	Surface mount, on reels	6795	11	
511	M/A-COM	MD-4007	Mixer	Surface mount	115	30	
512	M/A-COM	MD-4010 PIN	Mixer	Mixer	12	36	
513	M/A-COM	MD-523-3	Mixer	Flatpack	10	27	
514	M/A-COM	MD-525-4 TNC	Mixer	TNC, High Level Double Balanced, RF/LO=5-4000 MHz, IF 5-1900 MHz, LO Drive +10 dBm, Conversion Loss 9dB @ 5-2000 MHz, 10 dB @ 2000-4000 MHz, 1dB Comp Point +6 dBm	13	1	
515	M/A-COM	MD-924	Mixer	Northrop Grumman P/N 037-002895-001	4	29	5962013148369
516	M/A-COM	MD-936	Mixer	Mixer	7	27	
517	M/A-COM	MDC-156 SMA	Mixer	SMA Connectors	21	14	
518	M/A-COM	MDC-178 SMA	Mixer	RF/LO 2.6-5.2 GHz, IF DC-300 MHz, LO Drive +7 dBm, Conversion Loss 6 dB Max, 1dB Comp Point +2.5 dBm typical, SMA Female Connectors, Have Catalog Data Sheet	2	24	
519	M/A-COM	MDC-185 SMA	Mixer	RF/LO 3.7-4.2 GHz, IF DC-1300 MHz, LO Drive +7 dBm, Conversion Loss 5.0 dB, 1dB Comp Point +2 dBm SMA Female Connectors	4	24	
520	M/A-COM	MDC-186 SMA	Mixer	SMA, 0-3, 4-8 and 4-11 GHz, -55 to +85 Deg C, 1.14 X 0.39 X 0.93 Inches	2	24	5895013488640
521	M/A-COM	MDS-148	Mixer	SF-1 Surface Mount package, RF/LO=10-1500, IF=DC-1500MHz, Have Catalog Data Sheet, LO Drive +10 dBm, Conversion Loss 10-800 @ 7.5 dB Max, 8000-1500 @ 10 dB Max, Isolation 40 dB, Input P1dB=+5 dBm	2	37	
522	M/A-COM	MD-S5010	Mixer	Double Balanced, 1108-00001 Rev A, Customer part number 109710-1	6	23	
523	M/A-COM	MD-S5018	Mixer	CPN TPR-30-027-01B, flatpack, Cassini program	6	23	
524	M/A-COM	MD-S5019	Mixer	8-Pin Flatpack, Also P/N POTL-3007-01B	19	23	
525	M/A-COM	MD-S5021	Mixer	CPN POTL3022-01-B	4	23	
526	M/A-COM	MDS-S5024-QM	Mixer	Surface mount	7	23	
527	M/A-COM	MLF-3 PIN	Mixer	RF/LO 0.02-200 MHz, IF DC-200 MHz, Conversion Loss 5.5 dB, LO Drive +7 dBm, 1 dB Comp Point +4.5 dBm, RH-2 Package, Have Data Sheet	4	33	
528	M/A-COM	MX05-9003-00	Mixer	Flatpack, 8.5-10.5 GHz, SSM118-001	3	24	
529	M/A-COM	MX08-9001	Mixer	SMA, Markings, R,L,IF1,IF1	1	24	
530	M/A-COM	MX10-9007-00	Mixer	RF 5.85-6.425 GHz	11	24	
531	M/A-COM	MX10-9018-00	Mixer	Mixer	5	24	
532	M/A-COM	MX05-8003-00	Mixer??	SSM1188-001	4	24	
533	M/A-COM	PM-101	Modulator	Bi-phase, 10-750 MHz, TO-8-1, current driven, BPSK	47	37	
534	M/A-COM	PM-108 PIN	Modulator	QPSK, 50-100MHz Flatpack D/C 9513	33	24	5962012716076
535	M/A-COM	PM-110 TIB	Modulator	QPSK, 50-100MHz Flatpack	40	27	
536	M/A-COM	PM-579	Modulator	Bi-Phase Modulator, 10 to 750 MHz, Sperry PN 7918298-00 , +5 VDC	3	37	
537	M/A-COM	PM-581	Modulator	Phase Modulator for Paramax	2	27	
538	M/A-COM	PM-583	Modulator	Phase Modulator for Evergo	6	27	
539	M/A-COM	PM-669	Modulator	Quadriphase Mod/Demod, G283422-1 , 50-100 MHz, I.L 6.25 dB, Amp Bal 0.5 dB, VSWR 1.2/1.4, Phase Deviation 6.5 Deg, Flatpack, Port Markings In/Out, D1, D2, D3, D4	6	8	
540	M/A-COM	FM-104G	Multiplier	Flat pack	4	5	
541	M/A-COM	FM-106	Multiplier	X2, 200-3000 In, 400-6000 MHz out, Hermetic flatpack, FP-2 pkg	2	36	
542	M/A-COM	FM20-0004-PB7	Multiplier	Aeroflex	6	27	
543	M/A-COM	FM-527	Multiplier	Doubler, 75-1500 MHz In, 150-3000 MHz out, flatpack, Input Power +13 dBm Max	1	36	5895013169091
544	M/A-COM	FM-531	Multiplier	Westinghouse 586R628H01	2	37	
545	M/A-COM	FM-540	Multiplier	Frequency Tripler, 75-1500 In, 225-4500 Out, Hughes 970108-2	2	27	
546	M/A-COM	FM-545	Multiplier	X3, 75-1500 In, 225-4500 MHz out, +13 dBm, Westinghouse PN 1A20158H01, Flatpack, 10-Pin	14	36	5962013563413
547	M/A-COM	FM-560	Multiplier	Frequency Multiplier	4	24	
548	M/A-COM	SA-513-3	Multiplier	Multiplier or Supercomponent	1	30	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
549	M/A-COM	SA588	Multiplier	45-49MHz in, 4X, 1A20959H01	2	30	
550	M/A-COM	4511-1315-00	Open	OSP Plug	15	11	
551	M/A-COM	4512-1315-00	Open	OSP Jack	1	26	
552	CTI	C-4308	Oscillator	Cavity Tuned, 20 VDC, Currently set to 4730 MHz, but tunable from 4550-5000 MHz	2	31	
553	CTI	C-4308	Oscillator	Cavity Tuned, 20 VDC, Currently set to 4920 MHz, but tunable from 4550-5000 MHz	3	31	
554	PES	PV2920	Oscillator	VT, Vcc, RF connections, Surface Mnt, Voltage Tunable, Possibly 2900 MHz, 20 MHz tuning	377	43	
555	TYCO AXICOM	V23105-A5003-A201	Relay	DPDT, 12 VDC, DIP Configuration, PC Board mount, data sheet	25	24	
556	Vishay	SOGC2003101G	Resistor Network	Thick Film Resistor Network, SMT, Data Sheet @ www.vishay.com, CPN 09958294	1459	25	
557	BOURNS	3329H-1-102	Resistor, Variable	Trimmer, 1K Ohms, Single Turn, 1/4 inch Round, Top Aligned, Data Sheet Available	400	42	
558	M/A-COM	1020-1314-02	Short	SSMA Jack, Stainless	14	21	
559	M/A-COM	1021-1314-00	Short	SSMA Plug	1	30	
560	M/A-COM	2020-1312-00	Short	SMA Female w/2" monel bead chain, Gold Plated	5	3	5985011547443
561	M/A-COM	2020-1312-02	Short	SMA Female w/2" monel bead chain, Stainless	21	3	
562	M/A-COM	3001-1312-02	Short	N Male with chain	1	26	
563	M/A-COM	3101-1312-02	Short	TNC Male with chain	1	26	
564	M/A-COM	3102-1312-02	Short	TNC Female with chain	8	21	
565	M/A-COM	3102-1314-02	Short	TNC Female	19	12	5935010994991
566	M/A-COM	3201-1312-02	Short	BNC Plug with chain	20	10	
567	M/A-COM	3202-1312-02	Short	BNC Jack with chain	5	41	
568	M/A-COM	4511-1314-00	Short	OSP Plug	2	26	
569	M/A-COM	4512-1314-00	Short	OSP Jack	2	30	5935014166736
570	M/A-COM	4720-1314-00	Short	OSSP Jack	1	29	
571	M/A-COM	8520-6002-00	Short	OS-50 Male	1	27	
572	M/A-COM	CN21-0001-40S	Short	IAW 3261883-22 SMA Male Short. Have drawing/spec for complete series.	30	4	
573	M/A-COM	1298-4004-40	Spacer or Cap	Specs unknown	400	6	
574	M/A-COM	SA-543	Supercomponent	Specs unknown	77	20	
575	M/A-COM	21ST1	Switch	Specs unknown	1	A	
576	M/A-COM	8438-S692	Switch	SMA SP5T, 15-213 MHz, +5, -12VDC, 800 nsec, IL2.1, Isol 65, VSWR 1.5	4	21	
577	M/A-COM	SW-111	Switch	SPST, DIP, TTL, 20-2000 MHz, Hermetic DI-1 Pkg, 2 usec, Have Data Sheet	3	32	
578	M/A-COM	SW-113 PIN	Switch	DIP Package	18	21	
579	M/A-COM	SW-121 PIN	Switch	SPST, 10-1000MHz, TTL, Hermetic, DIP, Usable to 2 GHz, DI-1 package, Isol=60dB	31	37	
580	M/A-COM	SW-122	Switch	SPDT, DIP package, TTL or CMOS?	11	21	
581	M/A-COM	SW-128PIN	Switch	GaAs, SP4T Reflective, 0.1-2GHz, MMIC, w/drive, 16-lead DIP	43	15	
582	M/A-COM	SW13-0004-S	Switch	Alcatel Espace 39758023 Rev B	7	23	
583	M/A-COM	SW13-0005-S	Switch	SPDT flat pack, TRW Spec 1YB48-001S0889	11	23	
584	M/A-COM	SW-133 PIN	Switch	DIP Package, SP3T up to 1.8 GHz	13	30	
585	M/A-COM	SW-134 PIN	Switch	DIP Package, SP4T up to 1.8 GHz	16	30	
586	M/A-COM	SW-137PIN	Switch	SPDT, GaAs, Reflective, .01-3GHz, DIP package, Integrated ASIC driver, Data Sheet	2	33	
587	M/A-COM	SW15-0009	Switch	Hazeltine 1006166P	1	32	
588	M/A-COM	SW-161 PIN	Switch	DIP, 10-1500, SPST, Internally terminated, TTL	4	32	
589	M/A-COM	SW18-0003-S	Switch	SP4T flatpack, NorthropGrumman 589R241H06	3	23	
590	M/A-COM	SW19-0001-S	Switch	SP6T flatpack, -5V, +5V, 589R241H08	3	23	
591	M/A-COM	SW-206 PIN	Switch	SPDT GaAs, Absorptive, 5-3000 MHz, CMOS Driver, Data Sheet	1	33	
592	M/A-COM	SW-207 T1	Switch	SPDT GaAs, 5-3000 MHz, TTL, 20 nsec, DIP Pkg, Bias +5VDC, Usable to 4 GHz, Data Sheet	1	8	
593	M/A-COM	SW-215 T1B	Switch	SPST GaAs, 5-3000MHz, Absorptive, 20 nanoseconds, TTL, DIP Package, Data Sheet	7	20	
594	M/A-COM	SW-216 PIN	Switch	SPST, GaAs, Absorptive, 5-3000MHz, CMOS Ctrl, DIP Package, Data Sheet	4	33	
595	M/A-COM	SW-235	Switch	SPDT, Flatpack, GaAs, 5-3000 MHz, Isolation 50 dB	1	33	
596	M/A-COM	SW-242	Switch	SP3T, GaAs, 5-2000 MHz, Isolation 60 dB, Insertion Loss 1.0 db	34	A	
597	M/A-COM	SW-244	Switch	SP3T, GaAs, 5-3000 MHz	54	A	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
598	M/A-COM	SW-256PIN	Switch	Unknown	9	20	
599	M/A-COM	SW-257PIN	Switch	SP4T, 5-2000 MHz, 5-2000 MHz	3	20	
600	M/A-COM	SW-258 PIN	Switch	SP4T, GaAs	5	37	
601	M/A-COM	SW-264 PIN	Switch	SP4T flatpack, 5-2000 MHz	28	28	
602	M/A-COM	SW-313 SD	Switch	SPDT, GaAs, Absorptive, DC-3, TTL/CMOS Control, Surface Mount, Data Sheet, DC9906	6	33	
603	M/A-COM	SW-313B	Switch	SPDT, GaAs, Absorptive, DC-3GHz, TTL/CMOS, flatpack, Insertion Loss=0.9 dB, Isolation=50 dB, Data Sheet	8	29	
604	M/A-COM	SW-314B	Switch	SP4T Surface Mount, GaAs MMIC, Absorptive, DC-3 GHz, TTL, 24-lead ceramic surface mount pkg, Insertion Loss 1.4 dB, Isolation 45 dB, Data Sheet	5	33	
605	M/A-COM	SW-314TB	Switch	SP4T, GaAs Absorptive, DC-3 GHz, TTL, on test board w/ SMA Connectors, Data Sheet	5	20	
606	M/A-COM	SW-367 SMA	Switch	SPST, SMA, DC-2 GHz, High Isolation GaAs Absorptive, TTL, 5 nsec, 5 volt, have data sheet	9	34	
607	M/A-COM	SW-368 PIN	Switch	Transfer, TO-5, 5-2000 MHz, Max Power +33 dBm	6	33	
608	M/A-COM	SW-613	Switch	SPDT, Teledyne Electronics 50-200 MHz, 12 VDC, 0.13msec, 24 Pin	2	8	5985013397341
609	M/A-COM	SW-677	Switch	Customer=TRW	1	20	
610	M/A-COM	SW-683	Switch	CPN 2693166-1	1	28	
611	M/A-COM	SW-826	Switch	Flatpack, for Hazeltine	8	25	
612	M/A-COM	SW-840	Switch	Cust=E-Systems, SMA, SPDT	1	20	
613	M/A-COM	SW-843	Switch	DIP, Westinghouse / Northrop Grumman 1A20917H02, goes in ARSR-4	2	32	5930014479801
614	M/A-COM	SW-857	Switch	SPDT, TO, 0.3-2000 MHz	3	32	
615	M/A-COM	SW939	Switch	TO-8	1	20	
616	M/A-COM	SW-951	Switch	SP4T Solid State, Argo 193085-1	1	19	
617	M/A-COM	SW-975	Switch	Flatpack	10	29	
618	M/A-COM	SW-976	Switch	Loral, TO-5	4	8	
619	M/A-COM	SW-979	Switch	900-1400MHz flatpack, Customer P/N185A474	3	19	
620	M/A-COM	SW-S5004	Switch	SP3T, Dual FET, CPN 109304-1, 1Y72B-001E-758	4	23	
621	M/A-COM	SW-S5005	Switch	SPN 1098-00001 Customer Part Number 109304-2	18	23	
622	M/A-COM	SW-S5017	Switch	SPDT flatpack, 589R241H02, GaAs	4	23	
623	M/A-COM	SW-S5021	Switch	Flatpack, TTL, for TRW	2	23	
624	M/A-COM	SW-S5022	Switch	SP3T Dual FET, surface mount, CPN109304-1 Rev3, 1Y72B-001E-758	4	23	
625	M/A-COM	SW-S5023	Switch	SP6T, GaAs Hybrid, Customer part Number 1Y73B-001E-758	2	23	
626	M/A-COM	SW-S5029	Switch	SP2T Surface Mount, 1YB02-001W-785	1	23	
627	M/A-COM	6510-10	Switch, Electromechanical	SP6T, TTL, 100 nsec, SEDCO 0450006-1, IL 3.3, VSWR 1.5, Isol 55	1	21	
628	M/A-COM	7524-6132-00	Switch, Electromechanical	N, SPDT, 28 VDC Electromechanical, DC-12.4 GHz, Failsafe	12	5	
629	M/A-COM	7530-6112-00	Switch, Electromechanical	SMA SPDT Failsafe, Electromechanical, 24-28 VDC	10	4	
630	M/A-COM	7530-6313-10	Switch, Electromechanical	SMA SPDT, Electromechanical	12	1	
631	M/A-COM	7530-6415-01	Switch, Electromechanical	SMA SPDT Latching, DC-18 GHz, TTL, Diodes, 12 VDC, Solder Terminals	6	4	
632	Charter Engineering	SM-C-740434	Switch, Electromechanical	SMA, SP6T, Normally Open, DC-18 GHz, 28 VDC, Isolation 60 dB, Solder Posts	15	46	5985014422641
633	M/A-COM	SW-972 SMA	Switch, GaAs	SMA, SPDT, 0 to 3 GHz, -5, +5 VDC, CMOS TTL (SW-313 inside case), Isolation 50 dB	174	14	
634	M/A-COM	2664-0107-20	Switch, PIN Diode	SPDT SMA Reflective, 1-2 GHz, TTL, Gnd, E1, -15, +15	1	24	
635	M/A-COM	2664-1003-00	Switch, PIN Diode	SPDT Reflective, E1, -12V, +5V, 0.5-2.0GHz, 60 dB Isol, 30 nsec, 0.1 Watts	1	A	
636	M/A-COM	2666-9010	Switch, PIN Diode	SMA SPDT, +5, -12, Control, IL 1.20, Isol 50, Return Loss 11.5	1	21	
637	M/A-COM	2684-1003-10	Switch, PIN Diode	SMA, 6-18 GHz, Reflective, with driver and removable connectors, microwave	1	29	
638	M/A-COM	1041-6203-00	Tee	SSMA, DC-18, 1/2 watt, with chain, F-M-F	3	29	5935011102926
639	M/A-COM	2041-4016-00	Tee	SMA F-F-F	1	21	
640	M/A-COM	2041-4017-02	Tee	SMA F-M-F	11	26	5935000052574
641	M/A-COM	2041-4055-43	Tee	SMA F-M-F	11	27	
642	M/A-COM	2041-4060-43	Tee	SMA F-F-F CPN 3282809-4	9	27	
643	M/A-COM	2041-4061-43	Tee	SMA M-F-M 3282809-5	5	27	
644	M/A-COM	2041-6204-02	Tee	SMA M-F-M, unmatched, non-isolated, Passivated Stainless	17	1	5935012937513

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
645	M/A-COM	2042-6205-00	Tee	SMA MMM, Matched, 7.5-10 GHz, 1.6" X 1.28"	3	24	
646	M/A-COM	2047-6013-00	Tee	Monitor Tee/DC Block, SMA, 4-11 GHz, 600 Volts, 20 Watts	1	26	
647	Natl Semiconductor	LM50BIM3CT-ND	Temperature Sensor	Temp Sensor, SOT-23 pkg, Price 1-99 @ \$.80 ea, 100-1595@ \$.50 each	1405	810	
648	M/A-COM	2001-4033-02	Termination	SMA Male, DC-18 IAW HAC 723398-30	1	21	5985011846571
649	M/A-COM	2001-4036-00	Termination	SMA Male, DC-12.4, w/chain	10	21	5985010732974
650	M/A-COM	2001-4040-00	Termination	SMA Male, DC-18, 1 Watt, VSWR 1.15 @ 18	1	24	
651	M/A-COM	2001-4068-00	Termination	SMA Male with chain, microwave, IAW Raytheon 713552-1	1	22	5985013224932
652	M/A-COM	2001-4094-00	Termination	SMA Male with protected chain, IAW Army drawing 11748209	1	22	5985011354766
653	M/A-COM	2001-4133-00	Termination	SMA Male, DC-18, with chain	1	22	
654	M/A-COM	2001-4281-40	Termination	SMA with screw on back? 2A007-007V-001	4	4	
655	M/A-COM	2001-4294-00N	Termination	SMA Male, DC-19, M39030/3-12N	1	26	
656	M/A-COM	2001-4296-02	Termination	SMA Male, DC-12.4, (53711)6166779	2	22	5985012672282
657	M/A-COM	2001-4303-00N	Termination	SMA Male, DC-10, M39030/3-10N	13	21	5985012402330
658	M/A-COM	2001-4304-00S	Termination	SMA Male with chain, DC-19 GHz, M39030/3-13S	7	26	5985013660171
659	M/A-COM	2001-4312-02	Termination	SMA Male, DC-18, 1 Watt	1	22	
660	M/A-COM	2001-4425-94	Termination	High Power Load Block with SMA Male and 13" RG142 coax on other end	8	29	
661	M/A-COM	2001-4439-02	Termination	SMA Male, 026-007-005, microwave	1	22	
662	M/A-COM	2001-6148-00	Termination	SMA Male, DC-18, 1/2 Watt, with chain	8	26	
663	M/A-COM	2002-4075-15	Termination	SMA Female, microwave	37	45	
664	M/A-COM	2002-6101-02	Termination	SMA Female, DC-18, 1 Watt, VSWR 1.2@18, L=0.53, 0.250 Hex	10	3	
665	M/A-COM	2002-6105-02	Termination	SMA Female, DC-18, 1 Watt, with chain	10	22	
666	M/A-COM	2002-6110-02	Termination	SMA Female, DC-26.5, 1/2 Watt, 1.3 VSWR @ 26.5	5	14	
667	M/A-COM	2002-6111-02	Termination	SMA Female, DC-18, 1/2 watt, 1.1 VSWR @ 18	2	13	
668	M/A-COM	2002-6113-02	Termination	SMA Female, DC-18, 1/2 watt, 1.3 VSWR @ 18 GHz	61	18	5985001920138
669	M/A-COM	2002-6116-02	Termination	SMA Female, DC-12.4, 1/2 watt	8	21	
670	M/A-COM	2002-6500-00	Termination	SMA Female, DC-4, 1/2 watt	2	26	
671	M/A-COM	2002-6500-94	Termination	SMA Female, DC-4, 1/2 watt	2	26	
672	M/A-COM	2003-6117-02	Termination	SMA Male, DC-18, 1/2 watt	2	26	
673	M/A-COM	2003-6500-00	Termination	SMA Male, Gold Plated	1	36	
674	M/A-COM	2004-6118-00	Termination	SMA Female, DC-18 GHz, with Calibration Card	1	46	
675	M/A-COM	2068-4014-02	Termination	4-hole flange, Pin, microwave	2	26	
676	M/A-COM	2068-6102-00	Termination	SMA Flange Mt, DC-18, 1/2 Watt, "A" slot, Slot=0.20 (.5mm)	1	21	
677	M/A-COM	2068-6121-10	Termination	Flange for SMA, microwave	106	3	
678	Florida RF Labs	22-0002	Termination	Pill Shaped, Stripline, DC-18 GHz, 3 Watts, Gold Finish, Mil-E-5400, -55 to +125C, Data Sheet Available	156	45	
679	M/A-COM	3001-6100-00	Termination	N Male, DC-18, 2 Watts, L=1.44", Passivated Stainless	3	10	5985012357796
680	M/A-COM	3101-4073-43	Termination	TNC Male, CPN 23001827P2	7	41	
681	INMET	3111-296LTD	Termination	N Female, DC-2.3 GHz, 150 Watts CW, Baseplate Mounted, 50 Ohm, 2.59 X 2.00 X 0.98 inches, Full Data Sheet Available.	14	39	
682	M/A-COM	3201-1316-00	Termination	BNC Male, with chain, 50 Ohms	13	9	5895013308639
683	M/A-COM	3202-6100-00	Termination	BNC Female	13	41	
684	M/A-COM	4501-6113-00	Termination	OSP Plug, DC-18, 0.5 watt, VSWR@18=1.3	79	13	
685	M/A-COM	4501-6115-00	Termination	OSP Plug, DC-18, 0.5 watt, VSWR@18=1.3, with chain	1	21	
686	M/A-COM	4502-6111-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.1	26	13	
687	M/A-COM	4502-6112-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.2	54	15	
688	M/A-COM	4502-6113-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.3	368	6	
689	M/A-COM	4506-4001-00	Termination	OSP Jack Flange Mount, DC-18, 0.5 watt	3	21	
690	M/A-COM	4510-6110-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.2, compression spring	125	11	5985014910709
691	M/A-COM	4510-6112-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.2, compression spring	30	10	

	A	B	C	D	E	F	G
3	Manufacturer	Part Number	Item Name	Specifications	Qty	Bin	NSN
692	M/A-COM	4510-6113-00	Termination	OSP Jack, DC-18, 0.5 watt, VSWR@18=1.3, compression spring	26	41	
693	M/A-COM	4512-6111-00	Termination	OSP Jack, DC-18, VSWR@18=1.1	5	26	5985014162926
694	M/A-COM	4701-6111-00	Termination	OSSP Plug, DC-18, 0.5 watt, VSWR@18=1.1	10	29	
695	M/A-COM	4701-6112-00	Termination	OSSP Plug, DC-18, 0.5 watt, VSWR@18=1.2	1	29	
696	M/A-COM	4701-6115-00	Termination	OSSP Plug, DC-18, 0.5 watt, VSWR@18=1.3, with chain	10	29	
697	M/A-COM	4702-6111-00	Termination	OSSP Jack, DC-18, 0.5 watt, VSWR@18=1.1	8	29	
698	M/A-COM	4702-6112-00	Termination	OSSP Jack, DC-18, 0.5 watt, VSWR@18=1.2	1	29	
699	M/A-COM	4702-6113-00	Termination	OSSP Jack, DC-18, 0.5 watt, VSWR@18=1.3	28	41	
700	M/A-COM	4702-6115-00	Termination	OSSP Jack, DC-18, 0.5 watt, VSWR@18-1.3, with chain	4	21	
701	M/A-COM	5102-6155-02	Termination	Plug, microwave	7	22	
702	M/A-COM	9001-4001-40	Termination	Blind Mate	10	24	
703	M/A-COM	9002-4001-00	Termination	Blind Mate	3	29	
704	M/A-COM	9501-6001-00	Termination	Stripline, DC-18 GHz, 1 Watt	36	6	
705	Midisco	MDC1091M	Termination	SMA Male, DC-18 GHz, 1 Watt, VSWR 1.15 @ 18 GHz, L=0.35	3	B	
706	RF Industries	RF-1017	Termination	BNC Male, 50 Ohms, 1 Watt	5	C	
707	MACOM	TM20-0002-40	Termination	SMA?	52	22	
708	Midwest Microwave	TRM-2053M-NNN-02	Termination	N Male, DC-12.4 GHz, 2 Watts, with chain	3	46	
709	MACOM	9099-4029-80	Termination Box	Triac-type connector and two sample ports for DVM probes, Hughes 7742953-100-1	6	27	
710	MACOM	TP03-0004-FP1	Transformer, Pulse	1-250 MHz, TI P/N 772514-1	1	24	
711	MACOM	TP03-0005-S	Transformer, Pulse	CPN 560R880H01	10	23	
712	MACOM	TP-548	Transformer, Pulse	Specs unknown	15	28	
713	MACOM	TP-576	Transformer, Pulse	Specs unknown	2	24	
714	MACOM	4020-11M	Unknown	Specs unknown	8	24	
715	MACOM	6242-02-0102	Unknown	Specs unknown	94	34	
716	MACOM	AC-103	Unknown	Tiny flat pack, 7 leads, also P/N FM9900002	200	42	
717	MACOM	DMD2-4A	Unknown	Specs unknown	2	24	
718	MACOM	MA8498-1006E	Unknown	Specs unknown	202	4	
719	MACOM	MA8498-1006F	Unknown	Specs unknown	273	4	
720	MACOM	MA8498-6005B	Unknown	Specs unknown	27	4	
721	MACOM	MS-105 PIN	Unknown	Wilcox	4	27	
722	MACOM	SA-562	Unknown	For Raytheon/Hughes Part Number 654137	3	8	
723	M/A-COM	SA-563	Unknown	Hughes/Raytheon 82577-657820-1 Switch?	5	25	